

TIMBER WINDOWS

Profil 78 Rustic

Timber windows for traditional architecture, with classic glazing beads and visible timber on both sides, without aluminium components. The design can be adapted to arched windows, entrance doors and sliding doors. Glazing units up to 40 mm.

* Figures apply to the reference window specification described below.

Product overview

Profile	78 mm
Thermal transmittance Uw	0,98 W/(m²·K)*
Sound insulation Rw	35 dB*
Glazing	2 or 3 panes
Glazing unit thickness	Up to 40 mm
Opening direction	Inward opening
Manufacturer's stated warranty	5 years**

** The exterior coating warranty depends on the timber and coating type. Specific supply and warranty terms are set out in the quotation and contract.

Specification

Timber	Finger-jointed and solid pine, shorea, larch, eucalyptus, oak and other species
Coating system	Teknos
Aluminium components	No external aluminium cladding
Hardware	Roto or G.U.
Glass	Saint-Gobain
Seals	Schlegel Q-Lon
Handles	Hoppe Atlanta

How were the stated Uw and Rw values determined?

Reference window: 1230 × 1480 mm, inward opening, right-handed. Roto hardware with 7 locking points, 2 sealing contours and Schlegel seals. Glazing unit: 4-14Ar-4-14Ar-4, two low-emissivity panes, argon fill and aluminium spacer bars.

Different dimensions or specifications may change performance. Project-specific values are confirmed separately.