

TIMBER DOORS

Profil T78 Mira

Entrance doors with external aluminium cladding and rounded contours. The profile can be adapted to complex architectural designs and matching arched windows, entrance doors and sliding doors. Glazing units up to 48 mm.

* Figures apply to the reference window specification described below.

Product overview

Profile	78 mm
Thermal transmittance Uw	0,91 W/(m²·K)*
Sound insulation Rw	35 dB*
Glazing	2 or 3 panes
Glazing unit thickness	Up to 48 mm
Opening direction	Inward opening
Manufacturer's stated warranty	5 years**

** The exterior coating warranty depends on the timber and coating type. Specific supply and warranty terms are set out in the quotation and contract.

Specification

Timber	Finger-jointed and solid pine, shorea, larch, eucalyptus, oak and other species
Coating system	Teknos
Aluminium components	Gutmann
Hardware	Roto or G.U.
Glass	Saint-Gobain
Seals	Schlegel Q-Lon
Handles	Hoppe Atlanta

How should the stated Uw and Rw values be interpreted?

The source states values for doors dimensioned to customer requirements. Stated specification: inward opening, right-handed; Roto hardware with 7 locking points; 2 sealing contours and Schlegel seals; 4-14Ar-4-14Ar-4 glazing unit with two low-emissivity panes, argon and aluminium spacers.

Thermal and acoustic performance of each door structure is confirmed for its dimensions and selected specification.